




COLOR BODY PORCELAIN TILE

COLORS



White




Beige




Silver



Pearl



Grey



Mix ^

DECO



12" x 12"
Mosaic



12" x 12"
Pinnacle 3D



12" x 24"
Linear Brick



5" x 27"
Chevron




13" x 18"
Cold Industrial 3D



13" x 18"
Warm Industrial 3D




12" x 12"
Mosaic



12" x 12"
Pinnacle 3D



12" x 24"
Linear Brick



5" x 27"
Chevron



12" x 12"
Mosaic



12" x 12"
Pinnacle 3D



12" x 24"
Linear Brick



5" x 27"
Chevron



12" x 12"
Mosaic



12" x 12"
Pinnacle 3D




12" x 24"
Linear Brick




5" x 27"
Chevron




12" x 12"
Mosaic



12" x 12"
Pinnacle 3D








12" x 24"
Linear Brick



5" x 27"
Chevron

White, Beige, Silver, Pearl & Grey available in Grip Finish
 Beige, Pearl & Grey available in Outdoor Paving - Thickness 20mm
 ^Mix Color only available in 30" x 60" size - Matte & Glossy Finish

AVAILABLE SIZES



FINISH

MATTE RECTIFIED
GRIP RECTIFIED

THICKNESS

9mm | 20mm

TRIM

2 7/8" x 35 3/8" Bullnose

INSTALLATION & MAINTENANCE

Recommended Grout Size - 1/8"

For regular cleaning, use a neutral liquid detergent with a soft sponge or microfiber cloth. Persistent stains can be removed with a slightly abrasive sponge; if necessary, use a specially formulated stain remover.

TECHNICAL DATA-FLOOR TILE ONLY

	<p>D.C.O.F. WET > 0.42 ANSI 137.1</p>	<p>WATER ABSORPTION ≤ 0.5% ASTM C373</p>	<p>CHEMICAL RESISTANCE UA-ULA-UHA ISO 10545-13</p>	<p>FROST RESISTANCE RESISTANT ISO 10545-12</p>	<p>BREAKING STRENGTH ≥ 1500 N ISO 10545-4</p>	<p>DEEP ABRASION ≤ 150 mm³ ISO 10545-4</p>
--	---	---	---	---	--	--

