











Creme Tan Grey

Coffee

## **AVAILABLE SIZES**

**FIELD:** 12" x 24", 12" x 12"


**DECO & TRIM:** 2" x 2" (12" x 12") Mosaic, 3" x 12" Bullnose, 6" x 12" Cove Base

**RECOMMENDED GROUT JOINT:** 3/32" or greater. All sizes modular with 3/16" grout joint (~5mm)

Grout joints of 1/8" or less, especially with larger format tiles or running bond patterns, may require floor flatness values in excess of the 1/4" in 10' (or 1/16" in 1.0') standard required by ANSI.

For patterns with running bond/brick joints patterns, STP recommends a maximum of 33% offset.

## **TECHNICAL SPECIFICATIONS**



D.C.O.F. WET

≥ 0.55

BOT 3000

WATER ABSORPTION

≤ 0.1%

ASTM C373

CHEMICAL RESISTANCE

CLASS A

ASTM C650

frost resistance

NO DAMAGE
ASTM C1026

Breaking Strength

≥ 400 LBF

ASTM C648

ABRASION RESISTANCE

Black

Class 4

ASTM C1027







FOR SERVICE OR SAMPLES CALL 1-800-536-9224 OR EMAIL SAMPLES@SPECIALTYTILE.COM