



FRAY



COLORED BODY PORCELAIN FLOOR TILE


**COLORS**



White



Ivory



Sand



Pearl



Taupe



Gray



Smoke



Tobacco



Black



Metal White




Metal Gray




Metal Black

**DECOS**


2" x 2" Mosaic




White




Ivory




Sand




Pearl




Taupe



Gray



Smoke



Tobacco



Black

1" x 4" Herringbone Mosaic



White



Ivory



Sand



Pearl



Taupe



Gray



Smoke



Tobacco



Black

6" x 7" Hexmark Mosaic



White



Ivory



Sand



Pearl



Taupe



Gray



Smoke




Tobacco




Black

1" x 6" Tatami Deco



Tatami Warm



Tatami Cold

\*Tatami Warm - Includes White, Sand & Pearl

\*Tatami Cold - Includes Pearl, Gray & Smoke



Metal White



Metal Gray



Metal Black



## AVAILABLE SIZES



2" x 2" Mosaic, Herringbone Mosaic and Cove Base NOT available in Metal White, Metal Gray & Metal Black.

## FINISH

MATTE PRESSED  
MATTE RECTIFIED (Only 24" x 48")

## THICKNESS

9mm

## TRIM

3" x 24" Bullnose  
6" x 12" Cove Base (8.5mm)


## INSTALLATION & MAINTENANCE

Recommended Grout Size - 3/16"

For regular cleaning, use a neutral liquid detergent with a soft sponge or microfiber cloth. Persistent stains can be removed with a slightly abrasive sponge; if necessary, use a specially formulated stain remover.



## TECHNICAL DATA



D.C.O.F.  
WET  
**> 0.42**  
ANSI A137.1

WATER  
ABSORPTION  
**≤ 0.5%**  
ASTM C373

CHEMICAL  
RESISTANCE  
**RESISTANT**  
ASTM C650

FROST  
RESISTANCE  
**RESISTANT**  
ASTM C1026

BREAKING  
STRENGTH  
**≥ 350 LBF**  
ASTM C648

