





# COLORBODY PORCELAIN TILE

## **COLORS**



White

## **DECOS**



1<sup>1/8</sup>" x 1<sup>1/8</sup>" Mosaic



11<sup>1/4</sup>" x 13" Triangles



14<sup>3/4</sup>" x 29<sup>1/2</sup>" Brick



11" x 21<sup>5/8</sup>" Brick 3D



Silver



1<sup>1/8</sup>" x 1<sup>1/8</sup>" Mosaic



11<sup>1/4</sup>" x 13" Triangles



14<sup>3/4</sup>" x 29<sup>1/2</sup>" Brick



11" x 21<sup>5/8</sup>" Brick 3D



Grey



1<sup>1/8</sup>" x 1<sup>1/8</sup>" Mosaic



11<sup>1/4</sup>" x 13" Triangles



14<sup>3/4</sup>" x 29<sup>1/2</sup>" Brick



11" x 21<sup>5/8</sup>" Brick 3D



Dark



1<sup>1/8</sup>" x 1<sup>1/8</sup>" Mosaic



11<sup>1/4</sup>" x 13" Triangles



14<sup>3/4</sup>" x 29<sup>1/2</sup>" Brick



11" x 21<sup>5/8</sup>" Brick 3D

#### **AVAILABLE SIZES**

30" × 60"

30" × 30"

15" x 30"

~ Size also available with Grip Finish in all colors.

**FINISH** 

MATTE RECTIFIED GRIP RECTIFIED

9.5mm

**THICKNESS** 

### **TRIM**

3" x 30" Bullnose 15" x 30" Stair Tread

# **INSTALLATION & MAINTENANCE**

Recommended Grout Size - 1/8"

For regular cleaning, use a neutral liquid detergent with a soft sponge or microfiber cloth. Persistent stains can be removed with a slightly abrasive sponge; if necessary, use a specially formulated stain remover.

#### **TECHNICAL DATA**



D.C.O.F. WET > **0.42** ANSI 137.1 WATER
ABSORPTION
FLOOR ≤ 0.1%
WALL >10%
ISO 10545-3

CHEMICAL RESISTANCE RESISTANT

ISO 10545-13

FROST RESISTANCE

RESISTANT
ISO 10545-12

BREAKING STRENGTH S ≥ 1500 N OUTDOOR PAVERS S ≥ 10000 N ISO 10545-4 ABRASION RESISTANCE

≤ **150 mm³**ISO 10545-6

STPTILE.COM | 1-800-536-9224 | SAMPLES@SPECIALTYTILE.COM



